

Finishing Product Screener

L520s-3



STANDARD FEATURES

- 20x5 heavy duty high energy 2 bearing 3-deck screenbox
- 130Hp diesel engine
- Tracked
- Integrated hydraulic folding stockpiling conveyors
- 3-deck auxiliary conveyor attaches to machine for one unit transport
- Remote control tipping grid
- Fast on-site setup time - 15 minutes

SCREENBOX

Dimensions Top Deck	6100mm x 1524mm
Dimensions Middle Deck	6100mm x 1524mm
Dimensions Bottom Deck	5490mm x 1524mm
Screens Top Deck	5' x 4' side tension - 5 off
Screens Middle Deck	5' x 4' side tension - 5 off
Screens Bottom Deck	5' x 6' side tension - 3 off
Screen Angle	20 - 30 deg
Speed Adjustable	YES - Pressure compensated FCV
Screen Stroke Adjustable	10mm

HOPPER

Hopper Volume	10.01m ³
---------------	---------------------

BELT FEED CONVEYOR

Belt Width	1200mm
Adjustable Speed	YES

MAIN CONVEYOR

Belt Width	1050mm
Angle Adjustable	YES

CONVEYOR

Stockpile Height	4638 - 4905mm
Belt Width	1200mm

ENGINE

Engine	CAT C4.4
Engine Power	97kW
Fuel Tank Capacity	399L
Hydraulic Tank Capacity	630L

DIMENSIONS

Transport Length	18.45m
Transport Width	3.22m
Transport Height	3.45m (Tracked)
Operation Length	19.60m

TOTAL WEIGHT	38,780 KG (EST.)
---------------------	-------------------------