

Finishing Product Screener

L622s-3



STANDARD FEATURES

- 22x6 heavy duty high energy 2 bearing 3-deck screenbox
- 225Hp CAT engine Tier 3 or 4f, 218Hp Volvo Tier 4 engine
- Track mobile
- Integrated hydraulic folding stockpiling conveyors
- Remote control tipping grid
- Fast on-site setup time - 15 minutes typically

SCREENBOX

Dimensions Top Deck	6710mm x 1830mm
Dimensions Middle Deck	6710mm x 1830mm
Dimensions Bottom Deck	6100mm x 1830mm
Screens Top Deck	6' x 4' side tension 5 off, 6' x 2' side tension 1 off
Screens Middle Deck	6' x 4' side tension 5 off, 6' x 2' side tension 1 off
Side Tension Bottom Deck	6' x 4' side tension 5 off
End Tension Bottom Deck	6' x 6' 8" end tension 3 off
Screen Angle	18 - 25 deg
Speed Adjustable	YES - pressure compensated FCV
Screen Stroke Adjustable	10mm

HOPPER

Hopper Volume	8m ³ / 10m ³
---------------	------------------------------------

BELT FEED CONVEYOR

Belt Width	1200mm
Adjustable Speed	YES

CONVEYOR

Belt Width	1200mm
Angle Adjustable	OPTION

CONVEYOR

Stockpile Height	4992mm
Belt Width	1400mm

ENGINE

Engine	CAT C7
Engine Speed	1800rpm
Fuel Tank Capacity	485L
Hydraulic Tank Capacity	800L

DIMENSIONS

Transport Length	19.55m
Transport Width	3.66m
Transport Height	3.6m
Operation Length	20.55m

TOTAL WEIGHT	42,430 KG (EST.)
---------------------	------------------